

# 1234P PERFORATED & 1234C CUSHIONED TILE SPECIFICATIONS

**Note: Due to variations in recycled materials from shipment to shipment, the following specifications are a median description only. Actual specifications with regard to density, brittleness, elongation and tensile strength may vary as much as 15% above or below the median figures represented below.**

## **MECHANICAL SPECIFICATIONS:**

**Size:-----12" X 12"**

**Thickness:-----Approximately 3/4"**

**Weight:----- 1234P-1.35 lbs. 1234C 1.5 LBS.**

**Flammability:--- ( ASTM 648-class 2, MFA 253, NBSIR 75-950) Yes**

**Material: -----100% Recycled cable PVC with UV stabilizers**

**Colors: Navy Blue, Royal Blue, Light Blue, Forest Green, Yellow, Dark Gray, Light Gray, Red, Black**

**Density ( ASTM D 792-88): ----- 1.3grams/cc**

**Brittleness/Temp (ASTM D745-73):----- -24 degrees C**

**Elongation (ASTM D638-77):----- 350%**

**Tensile Strength (ASTM D2863-77): ----- 2000 psi**

**Waterproof ----- Yes**

**Also resistant to: Oil, gasoline, most solvents, caustics, mold, mildew, water, ozone abrasion aging. Retards development of bacteria.**

*\*Color and tensile strength not effected by heat, cold, humidity or sunlight (except red).*