

SEO TECHNICAL DATA SHEET

SEO



ITEM SPECIFICATION



Coverdeck Systems SEO type pedestal for raised floors with adjustable height from 1.1" to 1.5" 28mm to 38mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.

PRODUCT RANGE

PRODUCT NAME	SEO
CHARACTERISTICS	Adjustable in highness. Bicomponent material (PP and rubber) self leveling head. Regulation key for highness adjustment Easy removable tabs Security lock system to prevent unlocking.
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	1.1"	28mm	+/- mm 1,0
MAXIMUM HEIGHNESS	1.5"	38mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	.57lbs	.260kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	40
PIECES PER PALLET	1800
BOX DIMENSION	15.5" x 13.25" x 18"
BOX WEIGHT	34lbs.
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com

SE1 TECHNICAL DATA SHEET

SE1



ITEM SPECIFICATION



Coverdeck Systems SE1 type pedestal for raised floors with adjustable height from 1.48" to 1.97" 37.5mm to 50mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.

PRODUCT RANGE

PRODUCT NAME	SE1
CHARACTERISTICS	Adjustable in highness. Bicomponent material (PP and rubber) self leveling head. Regulation key for highness adjustment Easy removable tabs Security lock system to prevent unlocking.
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	1.48"	37.5mm	+/- mm 1,0
MAXIMUM HEIGHNESS	1.97"	50mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	.71lbs	.320kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	30
PIECES PER PALLET	1350
BOX DIMENSION	15.5" x 13.25" x 18"
BOX WEIGHT	27lbs
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT	
	The product is simply laid on the laying area, with no need of any glue or fixing


The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com

SE2 TECHNICAL DATA SHEET

SE2



ITEM SPECIFICATION



Coverdeck Systems SE2 type pedestal for raised floors with adjustable height from 1.97" to 2.95" 50mm to 75mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.

PRODUCT RANGE

PRODUCT NAME	SE2
CHARACTERISTICS	Adjustable in highness. Bicomponent material (PP and rubber) self leveling head. Regulation key for highness adjustment Easy removable tabs Security lock system to prevent unlocking.
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	1.97"	50mm	+/- mm 1,0
MAXIMUM HEIGHNESS	2.95"	75mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	.78lbs	.352kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	25
PIECES PER PALLET	1125
BOX DIMENSION	15.5" x 13.25" x 18"
BOX WEIGHT	26lbs
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com

SE3 TECHNICAL DATA SHEET

SE3



ITEM SPECIFICATION



Coverdeck Systems SE3 type pedestal for raised floors with adjustable height from 1.97" to 2.95" 50mm to 75mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.

PRODUCT RANGE

PRODUCT NAME	SE3
CHARACTERISTICS	Adjustable in highness. Bicomponent material (PP and rubber) self leveling head. Regulation key for highness adjustment Easy removable tabs Security lock system to prevent unlocking.
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	2.95"	75mm	+/- mm 1,0
MAXIMUM HEIGHNESS	4.72"	120mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	1.01lbs	.458kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	25
PIECES PER PALLET	750
BOX DIMENSION	15.5" x 13.25" x 18"
BOX WEIGHT	32lbs
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com



SE4 TECHNICAL DATA SHEET

SE4



ITEM SPECIFICATION



Coverdeck Systems SE4 type pedestal for raised floors with adjustable height from 4.27" to 6.69" 120mm to 170mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.

PRODUCT RANGE

PRODUCT NAME	SE4
CHARACTERISTICS	Adjustable in highness. Bicomponent material (PP and rubber) self leveling head. Regulation key for highness adjustment Easy removable tabs Security lock system to prevent unlocking.
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	4.72"	120mm	+/- mm 1,0
MAXIMUM HEIGHNESS	6.69"	170mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	1.14lbs	.518kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	25
PIECES PER PALLET	750
BOX DIMENSION	15.5" x 13.25" x 18"
BOX WEIGHT	35lbs
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com



SE5 TECHNICAL DATA SHEET

SE5



ITEM SPECIFICATION



Coverdeck Systems SE5 type pedestal for raised floors with adjustable height from 6.69" to 8.46" 170mm to 215mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.

PRODUCT RANGE

PRODUCT NAME	SE5
CHARACTERISTICS	Adjustable in highness. Bicomponent material (PP and rubber) self leveling head. Regulation key for highness adjustment Easy removable tabs Security lock system to prevent unlocking.
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	6.69"	170mm	+/- mm 1,0
MAXIMUM HEIGHNESS	8.46"	215mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	1.34lbs	.609kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	25
PIECES PER PALLET	625
BOX DIMENSION	15.5" x 13.25" x 18"
BOX WEIGHT	39lbs
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com

SE6 TECHNICAL DATA SHEET

SE6



ITEM SPECIFICATION



Coverdeck Systems SE6 type pedestal for raised floors with adjustable height from 5.51" to 9.06" 140mm to 230mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.

PRODUCT RANGE

PRODUCT NAME	SE6
CHARACTERISTICS	Adjustable in highness. Bicomponent material (PP and rubber) self leveling head. Regulation key for highness adjustment Easy removable tabs Security lock system to prevent unlocking.
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	5.51"	140mm	+/- mm 1,0
MAXIMUM HEIGHNESS	9.06"	230mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	1.53lbs	.694kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	25 SE3 + 25 P1 Extensions = SE6
PIECES PER PALLET	TBD
BOX DIMENSION	15.5" x 13.25" x 18"
BOX WEIGHT	32lbs + 15lbs
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com

SE7 TECHNICAL DATA SHEET

SE7



ITEM SPECIFICATION



Coverdeck Systems SE7 type pedestal for raised floors with adjustable height from 7.28" to 10.83" 185mm to 275mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.

PRODUCT RANGE

PRODUCT NAME	SE7
CHARACTERISTICS	Adjustable in highness. Bicomponent material (PP and rubber) self leveling head. Regulation key for highness adjustment Easy removable tabs Security lock system to prevent unlocking.
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	7.28"	185mm	+/- mm 1,0
MAXIMUM HEIGHNESS	10.83"	275mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	1.66lbs	.754kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	25 SE4 + 25 P1 Extensions = SE7
PIECES PER PALLET	TBD
BOX DIMENSION	14.5" x 13.375" x 18"
BOX WEIGHT	35 lbs + 15 lbs
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com



SE8 TECHNICAL DATA SHEET

SE8



ITEM SPECIFICATION



	<p>Coverdeck Systems SE8 type pedestal for raised floors with adjustable height from 9.25" to 12.8" 235mm to 325mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.</p>
--	---

PRODUCT RANGE

PRODUCT NAME	SE8
CHARACTERISTICS	<p>Adjustable in highness. Bicomponent material (PP and rubber) self leveling head.</p> <p>Regulation key for highness adjustment</p> <p>Easy removable tabs</p> <p>Security lock system to prevent unlocking.</p>
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	9.25"	235mm	+/- mm 1,0
MAXIMUM HEIGHNESS	12.8"	325mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	1.86lbs	.845kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	25 SE5 + 25 PI Extensions = SE8
PIECES PER PALLET	TBD
BOX DIMENSION	14.5" x 13.375" x 18"
BOX WEIGHT	39 lbs + 15 lbs
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com

SE9 TECHNICAL DATA SHEET

SE9



ITEM SPECIFICATION



Coverdeck Systems SE9 type pedestal for raised floors with adjustable height from 8.07" to 13.58" 205mm to 345mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.

PRODUCT RANGE

PRODUCT NAME	SE9
CHARACTERISTICS	<p>Adjustable in highness. Bicomponent material (PP and rubber) self leveling head.</p> <p>Regulation key for highness adjustment</p> <p>Easy removable tabs</p> <p>Security lock system to prevent unlocking.</p>
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	8.07"	205mm	+/- mm 1,0
MAXIMUM HEIGHNESS	13.58"	345mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	2.05lbs	.93kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	25 SE3 + 50 PI Extensions = SE9
PIECES PER PALLET	TBD
BOX DIMENSION	14.5" x 13.375" x 18"
BOX WEIGHT	32 lbs + Qty 2 15 lbs each
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com



SE10 TECHNICAL DATA SHEET

SE10



ITEM SPECIFICATION



	<p>Coverdeck Systems SE10 type pedestal for raised floors with adjustable height from 9.84" to 15.16" 250mm to 385mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.</p>
--	---

PRODUCT RANGE

PRODUCT NAME	SE10
CHARACTERISTICS	<p>Adjustable in highness. Bicomponent material (PP and rubber) self leveling head.</p> <p>Regulation key for highness adjustment</p> <p>Easy removable tabs</p> <p>Security lock system to prevent unlocking.</p>
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	9.84"	250mm	+/- mm 1,0
MAXIMUM HEIGHNESS	15.16"	385mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	2.18lbs	.99kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	25 SE3 + 50 PI Extensions = SE9
PIECES PER PALLET	TBD
BOX DIMENSION	14.5" x 13.375" x 18"
BOX WEIGHT	32 lbs + Qty 2 15 lbs each
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com



SE11 TECHNICAL DATA SHEET

SE11



ITEM SPECIFICATION



Coverdeck Systems SE11 type pedestal for raised floors with adjustable height from 11.81" to 15.75" 300mm to 400mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.

PRODUCT RANGE

PRODUCT NAME	SE11
CHARACTERISTICS	Adjustable in highness. Bicomponent material (PP and rubber) self leveling head. Regulation key for highness adjustment Easy removable tabs Security lock system to prevent unlocking.
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	11.81"	300mm	+/- mm 1,0
MAXIMUM HEIGHNESS	15.75"	400mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	2.38lbs	1.08kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	25 SE5 + 50 P1 Extensions = SE11
PIECES PER PALLET	TBD
BOX DIMENSION	14.5" x 13.375" x 18"
BOX WEIGHT	39 lbs + Qty 2 15 lbs ea
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com



SE12 TECHNICAL DATA SHEET

SE12



ITEM SPECIFICATION



Coverdeck Systems SE12 type pedestal for raised floors with adjustable height from 10.63" to 17.91" 270mm to 455mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.

PRODUCT RANGE

PRODUCT NAME	SE12
CHARACTERISTICS	Adjustable in highness. Bicomponent material (PP and rubber) self leveling head. Regulation key for highness adjustment Easy removable tabs Security lock system to prevent unlocking.
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	10.63"	270mm	+/- mm 1,0
MAXIMUM HEIGHNESS	17.91"	455mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	2.58lbs	1.17kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	25 SE3 + 75 P1 Extensions = SE12
PIECES PER PALLET	TBD
BOX DIMENSION	14.5" x 13.375" x 18"
BOX WEIGHT	32 lbs + Qty 3 15 lbs ea
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com



SE13 TECHNICAL DATA SHEET

SE13



ITEM SPECIFICATION



Coverdeck Systems SE13 type pedestal for raised floors with adjustable height from 12.4" to 19.69" 315mm to 500mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.

PRODUCT RANGE

PRODUCT NAME	SE13
CHARACTERISTICS	Adjustable in highness. Bicomponent material (PP and rubber) self leveling head. Regulation key for highness adjustment Easy removable tabs Security lock system to prevent unlocking.
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	12.4"	315mm	+/- mm 1,0
MAXIMUM HEIGHNESS	19.69"	500mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	2.71lbs.	1.23kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	TBD
PIECES PER PALLET	TBD
BOX DIMENSION	14.5" x 13.375" x 18"
BOX WEIGHT	TBD.
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com



SE14 TECHNICAL DATA SHEET

SE14



ITEM SPECIFICATION



Coverdeck Systems SE14 type pedestal for raised floors with adjustable height from 14.37" to 21.65" 365mm to 550mm, provided of bi-component self leveling head with anti noise and anti slip rubber on top. Pedestals are composed by a cylindrical base element of 8.07" 205mm diameter for resting on the laying surface, an intermediate screw with a locking security system, and a top head element with 4 easy removable tabs of h.12 mm in 2, 3 or 4 mm thickness. Base is provided of holes for water drainage and of 4 precut lines to facilitate any cutting of the base in case of need. Adjustment in highness is made with the exclusive regulation key that connects with the screw, as it is independent from both base and head.

PRODUCT RANGE

PRODUCT NAME	SE14
CHARACTERISTICS	Adjustable in highness. Bicomponent material (PP and rubber) self leveling head. Regulation key for highness adjustment Easy removable tabs Security lock system to prevent unlocking.
RAW MATERIAL	Polypropylene and rubber (head top finishing)
ENVIRONMENTAL IMPACT	recyclable material - non dangerous
APPLICATIONS SURFACES	On any waterproofing membrane, or any insulating panel or any compact and solid surface
APPLICATIONS AREA	Usable with any prefabricated self sustaining element for exterior flooring

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
BASE DIAMETER	8.07"	205mm	+/- mm 1,0
BASE THICKNESS	.2"	5mm	+/- mm 0,2
HEAD DIAMETER	4.33"	110mm	+/- mm 0,8

CHARACTERISTICS	VALUE / UNIT		TOLERANCE
LAYING SURFACE OF THE BASE	51.2"²	330cmq	+/- cmq 5
MINIMUM HEIGHNESS	14.37"	365mm	+/- mm 1,0
MAXIMUM HEIGHNESS	21.65"	550mm	+/- mm 1,5
TAB THICKNESS	.08" - .12" - .16"	2-3-4mm	+/- mm 0,2
TABS HIGHNESS	.47"	12mm	+/- mm 0,2
WEIGHT	2.91lbs	1.32kg	+/- 5%

TECHNICAL PROPERTIES		UNIT	VALUE
CENTRAL COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	19.93
ECCENTRIC COMPRESSION LOADING LIMIT RESISTANCE* (calculated at medium highness, between minimum and maximum extension)		KN	11.61
SLOPE CORRECTION		%	0-5
SHORE		Shore d	70 (+/-3)

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE
FIRE REACTION*	UNI EN 13501-1:2009	class	E
LOW TEMPERATURES REACTION			-40°

PACKAGING AND STORAGE	
PIECES PER BOX	25 SE5 + 75 P1 Extensions = SE14
PIECES PER PALLET	TBD
BOX DIMENSION	14.5" x 13.375" x 18"
BOX WEIGHT	39 lbs + Qty 3 15 lbs ea
PALLET DIMENSION	48" x 40" x 77"

LAYING OF THE PRODUCT
The product is simply laid on the laying area, with no need of any glue or fixing

The above data are relevant to current production and may be changed or updated by Coverdeck Systems at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Coverdeck Systems. All rights reserved.



Address: 408 A Meco Drive Wilmington, DE 19804
 Phone: (800) 550-3325
 (302) 427-7578
 Email: support@coverdeck.com
 Web: www.coverdeck.com