



# PEDESTAL SYSTEM



The SE adjustable pedestal system is a raised flooring product that combines exceptional aesthetics with superior technical features.

Recognized as the market's most exclusive solution for handling sloped installation surfaces, thanks to its tilting movements, the pedestal is capable of compensating for slopes of up to 5%.

Using the adjustment key this can be accomplished from above once the flooring has been installed to guarantee the precision alignment floor surface.

Along with other numerous additional advantages is making this pedestal system enjoyed daily by architects, builders, installers, and many more.

**FOR MORE INFORMATION**

**PLEASE CONTACT US:**


Phone: (800) 550-3325

(302) 427-7578

Email: [support@coverdeck.com](mailto:support@coverdeck.com)


[www.coverdeck.com](http://www.coverdeck.com)






### HIDES PIPES & SYSTEMS

Excellent for hiding pipes and systems while still maintaining easy access to inspect.




### SPEEDY INSTALLATION

The speed of installation provides an economic savings along with reduce time of inconvenience for inhabitants.




### SOUND REDUCTION

Due to the bi-component head the pedestal system is able to reduce sound level by up to 25dB.




### WEIGHT REDUCTION

With eliminating concrete screed, this elevated system creates a substantial reduction of weight on the structure.




### WATER OVERFLOW

The small space between plates allows the flow of water to convey through the slope below.




### THERMAL INSULATION

The space between flooring and underlying membrane allows a constant passage of air for a longer duration of waterproofing and thermal insulation.




### ABSORPTION OF EXPANSIONS

The independence of the flooring and of the supports allows to absorb expansions and the structural movements.




### ECO-FRIENDLY

The "dry" laying method does not require harmful adhesives or chemical products and can be easily removed and recycled without negative impact on the environment.



### ALWAYS LEVEL AND EASILY INSPECTABLE

Compensates for small differences in height and slope while the absence of mechanical fixings allows for easy inspections.



### STRONG WEIGHT RESISTANCE

The sturdy structure accomplished by continuous threading between base and screw provide a strong, safe and long lasting product.

## ACCESSORIES



Coupler



XL Head



Head Locking Latch



Shim  
1mm , 2mm , 3mm



Wood Joist Head

## SE PEDESTALS



SE0  
1.1" - 1.5"



SE1  
1.48" - 1.97"



SE2  
1.97" - 2.95"



SE3  
2.95" - 4.72"



SE4  
4.72" - 6.69"



SE5  
6.69" - 8.46"



SE6  
5.51" - 9.06"



SE7  
7.28" - 10.83"



SE8  
9.25" - 12.8"



SE9  
8.07" - 13.58"



SE10  
9.84" - 15.16"



SE11  
11.81" - 15.75"



SE12  
10.63" - 17.91"



SE13  
12.4" - 19.69"



SE14  
14.37" - 21.65"